



SAFETY DATA SHEET

According to EC Directive 1907/2006/EC, Article 31

Revision Date: 19/November/2010

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: Potassium Formate

Synonyms: KFormate; Formic acid, potassium salt

Use of the Substance/Preparation: Drilling fluids, Industrial Products

Supplier:

Cabot Specialty Fluids Waterway Plaza Two 10001 Woodloch Forest Drive Suite 275 The Woodlands, TX 77380 UNITED STATES Tel: 1-281-298-9955 Fax: 1-281-298-6190	Tantalum Mining Corporation of Canada, Ltd. Bernic Lake Box 2000 Lac du Bonnet, MB R0E 1A0 CANADA Tel: 1-204-884-2400 Fax: 1-204-884-2211	Cabot Specialty Fluids Ocean House Hareness Circle Altens Industrial Estate Aberdeen AB12 3LY SCOTLAND Tel: (+44) 1224-897229 Fax: (+44) 1224-870089
--	--	---

E-Mail Address: SDS@cabot-corp.com

Emergency Telephone Number: US: CHEMTREC 1-800-424-9300 or 1-703-527-3887
US: Other 1-978-663-3455
Canada: CANUTEC 1-613-996-6666

2. HAZARDS IDENTIFICATION

Indication of danger: Not a hazardous substance according to EC-Directive 67/548/EC, its various amendments and adaptations and EC-Regulation 1272/2008 (CLP)..

Principle Routes of Exposure: Inhalation, Eye contact, Skin contact, Ingestion

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause mechanical irritation. Avoid contact with eyes.

Skin Contact: May cause mechanical irritation. Avoid contact with skin.

Inhalation: Dust may be irritating to respiratory tract. Avoid breathing dust.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Carcinogenic Effects: Does not contain any substances listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union). See also Section 11.

Target Organ Effects: Eyes, Skin, Respiratory system

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorder

Potential Environmental Effects: No special environmental precautions required. See also Section 12.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	EINECS/ELINCS Number	Weight %	EU Classification
Potassium formate	590-29-4	209-677-9	97-98	None
Other alkali formates	Various	Not determined	< 3	None

4. FIRST AID MEASURES

Skin Contact:	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Seek medical attention if redness, swelling, itching, or burning occurs.
Eye Contact:	Flush eyes immediately with large amounts of water for 15 minutes. Seek medical attention if redness, swelling, itching, burning or visual disturbances occur.
Inhalation:	If cough, shortness of breath or other breathing problems occur, move to fresh air. Seek medical attention if symptoms persist. If necessary, restore normal breathing through standard first aid measures.
Ingestion:	Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person. Seek medical attention.
Notes to Physician:	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special Protective Equipment for Firefighters:	Wear suitable protective equipment. In the event of fire, wear self-contained breathing apparatus.
Specific Hazards:	None.
Hazardous Decomposition and/or Combustion Products:	Carbon monoxide, Carbon dioxide.
Risk of Dust Explosion:	Fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid dust formation. Ensure adequate ventilation. Use personal protective equipment. See also Section 8.
Methods for Cleaning Up:	Do not create a dust cloud by using a brush or compressed air. Clean up promptly by vacuum. Use a suitable vacuum cleaner. Pick up and transfer to properly labelled containers. See Section 13.
Environmental Precautions:	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. See also Section 13.

7. HANDLING AND STORAGE

Handling:	Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.
------------------	--

Storage: Hygroscopic material. Will absorb water readily from atmosphere. Keep away from humid air and water. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. Do not store together with strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

There are no exposure limits identified for this product. Exposure limits for dust are stated below.

Dust, or Particulates Not Otherwise Specified:	Austria MAK:	10 mg/m ³ , STEL 2x30 min, Inhalable dust 5 mg/m ³ , TWA, Inhalable dust
	Belgium:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
	France:	10 mg/m ³ , TWA Inhalable dust 5 mg/m ³ , TWA Respirable dust
	Germany - TRGS 900:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , Respirable fraction
	Ireland:	10 mg/m ³ , TWA, Total inhalable 4 mg/m ³ , TWA, Respirable
	Italy:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
	Spain:	10 mg/m ³ , VLA, Inhalable 3 mg/m ³ , VLA, Respirable
	Sweden:	10 mg/m ³ , NGV, Total inhalable 5 mg/m ³ , NGV, Respirable
	The Netherlands:	10 mg/m ³ , TGG, Inhalable 5 mg/m ³ , TGG, Respirable
	US ACGIH - TLV:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
	US OSHA - PEL:	15 mg/m ³ , TWA, Total inhalable 5 mg/m ³ , TWA, Respirable

ACGIH: American Conference of Governmental Industrial Hygienists

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Health and Safety Administration

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

TLV: Threshold Limit Value

TWA: Time Weighted Average

MAK: Maximale Arbeitsplatzkonzentration

OES: Occupational Exposure Standard

TRGS: Technische Regeln für Gefahrstoffe

(Technical Rule for Hazardous Materials)

ENGINEERING CONTROLS Ensure adequate ventilation to maintain exposures below occupational limits.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Approved respirator may be necessary if local exhaust ventilation is not adequate.

Hand Protection: Wear suitable gloves.

Eye Protection: Wear eye/face protection. Safety glasses with side-shields. Goggles.

Skin and Body Protection: Wear suitable protective clothing.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency eyewash and safety shower should be located nearby.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Powder
Odor:	None
Odor Threshold:	Not applicable
pH:	6.5-11 when dissolved in water
Relative Density:	1.910 g/cm ³
Specific Gravity:	Not determined
Vapor Density:	Not applicable
Boiling Point/Range:	Not applicable
Melting Point/Range:	Not determined
Vapor Pressure:	Not applicable
Water Solubility:	76.8% soluble at 20°C
Evaporation Rate:	Not applicable
Viscosity:	Not applicable
Partition Coefficient (n-octanol/water):	< 0 (no potential to bioconcentrate)
Flash Point:	Not determined
Explosion Limits in Air - Upper (g/m³):	Not determined
Explosion Limits in Air - Lower (g/m³):	Not determined
Autoignition Temperature:	Not determined
Flammability Classification:	Not determined
Decomposition Temperature:	Not determined
Oxidizing Properties:	Not determined

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Hazardous polymerization does not occur.
Mechanical Sensitivity (shock):	Not sensitive to mechanical impact.
Conditions to Avoid:	Avoid contact with strong oxidizing agents. During long exposures to high temperatures, and in contact with certain catalysts, some liberation of gasses (H ₂ and CO) might occur. The greatest risk exists when dry formate powder is contacted by a platinum catalyst. Users are advised to obtain the Cabot Specialty Fluid's (CSF) Formate Technical Manual, Section A13 from a CSF representative for more detailed information on conditions to avoid. CSF does not recommend retorting formate solutions to determine solids content as temperatures may exceed 500 °C. The use of rupture disks is recommended as a precautionary measure when conducting heat aging of formate solutions at temperatures above 150 °C.

Hazardous Decomposition and/or Combustion Products: Carbon dioxide, Carbon monoxide.

Static Discharge Effects: Avoid dust formation. Take precautionary measures against static discharges.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Oral LD50: LD50/oral/mouse = 5500 mg/kg.

Inhalation LC50:
Not determined.

Dermal LD50: Not determined.

STOT - Single Exposure: Not determined

Eye Irritation: Draize: Maximum average irritation score: 32.7 @ 1 hr, 7.3 @ 24 hr, 0.7 @ 48 hr. Moderate eye irritation.

Skin Irritation: Primary irritation index = 0.3. Slight irritation.

SUBCHRONIC TOXICITY

Not determined.

CHRONIC TOXICITY

Carcinogenic Effects: Does not contain any substances listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union).

STOT - Repeated Exposure: Not determined

OTHER

Mutagenic Effects: Not determined.

Reproductive Toxicity: Not determined.

Sensitization: Contains no known sensitizers.

Synergistic Materials: None reasonably foreseeable.

Aspiration Hazard: Not determined

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

MARINE

Juvenile turbot (*Scophthalmus maximus*) LC50 (96 hr) = 1700 mg/l
Marine algae (*Skeletonema costatum*) EbC50 (72 hr) = 3400 mg/l
Marine copepod (*Acartia tonsa*) LC50 (48 hr) = 300 mg/l
Brown shrimp (*Crangon crangon*) LC50 (96 hr) = 1300 mg/l

FRESHWATER

Rainbow trout (*Oncorhynchus mykiss*) LC50 (96 hr) = 3500 mg/l
Freshwater algae (*Scenedesmus subspicatus*) EbC50 (72 hr) = 1000 mg/l
Water flea (*Daphnia magna*) EC50 (48 hr) = 540 mg/l

Other Information: In the majority of marine species, this material has not demonstrated toxicity and has received a rating of GOLD/SILVER/SILVER for drilling products and GOLD for Completion/Workover products under the PARCOM Harmonized Offshore and Chemical Notification Format (HOCNF).

ENVIRONMENTAL FATE

Mobility: Highly soluble in water. Water solubility = 1200 g/L.

Bioaccumulation: Log Pow = <0 (no potential to bioconcentrate). See also Section 9.

Persistence / Degradability: Readily biodegradable
(Method: OECD 301D and 301E)

PBT and vPvB Assessment: This substance does not fulfill the criteria for PBT or vPvB

Other adverse effects: No other data are available

13. DISPOSAL CONSIDERATIONS

Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 3 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.

Product, as supplied, should be disposed of in accordance with the regulations issued by the appropriate federal, state and local authorities. Same consideration should be given to containers and packaging.

14. TRANSPORT INFORMATION

UN Number: Not regulated

UN Proper Shipping Name: Not regulated

UN Shipping Class: Not regulated

UN Packing Group: Not regulated

IMO IBC Code:

Potassium Formate - Pollution Category Z, Pollution Hazard Only, Not Requiring a Chemical Tanker.

IMDG (International Maritime Organization's Dangerous Goods Code):

Not regulated.

IATA

Not Regulated.

15. REGULATORY INFORMATION

Indication of danger: Not a hazardous substance according to EC-Directive 67/548/EC, its various amendments and adaptations and EC-Regulation 1272/2008 (CLP)..

EU Chemical Safety Assessment:

Per Article 14.1 of the REACH Regulation a Chemical Safety Assessment has been carried out..

EU Exposure Scenarios

Per Article 14.4 of the REACH Regulation no exposure scenario has been developed as the substance is not hazardous.

15. REGULATORY INFORMATION**International Inventories**

All components of this product are listed on or exempt from the following inventories:

- YES - Australian Inventory of Chemical Substances (AICS)
- YES - Canadian Domestic Substances List (DSL)
- YES - Chinese Inventory
- YES - European Inventory of Existing Commercial Chemical Substances (EINECS)
- NO - Japanese Inventory of Existing and New Chemical Substances (ENCS)
- NO - Korean Existing Chemicals List (KECL)
- YES - New Zealand Hazardous Substances and New Organisms Act (HSNO)
- NO - Philippines Inventory of Chemicals and Chemical Substances (PICCS)
- YES - United States Toxic Substances Control Act (TSCA) Inventory

Germany Water Endangering Class (WGK) Class

WGK ID Nr.: Not determined

Switzerland Giftklasse (Poison Class) Toxic Category**Chemical Name**

Potassium formate -- (tested and found to be not toxic): G-7498

16. OTHER INFORMATION**References:**

MARPOL 73/78, Latest edition of Marine Environment Protection Committee (MEPC) Circulars MEPC.2/Circular, IBC Code, IMO Resolution A.673(16) Guidelines for the Transport and Handling of Limited Amounts of Hazardous and Noxious Liquid Substances in bulk on Offshore Support Vessels.

Prepared by: Cabot Corporation - Safety, Health and Environmental Affairs
Revision Date: 19/November/2010
Previous Revision Date: 02/March/2009
Reason for Revision: New format to ensure compliance with 1272/2008/EC (CLP)

Disclaimer:

The information set forth is based on information that Cabot Corporation believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Cabot assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

® and 'TM' indicate trademarks of the Cabot Corporation.